

Exinda Network Orchestrator 4062 is our most powerful branch office appliance designed for customers with rapidly growing bandwidth needs and require the flexibility to upgrade in the future. The 4062 can be deployed as a 100 Mbps system and easily upgraded to 1 Gbps, with expandable network interfaces and remote management capabilities. If you're concerned about scaling to meet the future needs of your network, the 4062 is for you.

Network Diagnostics	Base	Expanded
Max APS Objects	150	250
Max SLA Objects	150	250
Max PDF Reports	30	60

Traffic Shaping	Base	Expanded
Max Shaping Throughput	1 Gbps	1 Gbps
Max Concurrent Flows	500,000	500,000
Max New Connections Rate	10,000/s	10,000/s
Max Traffic Policies	512	1024

Traffic Acceleration	Base	Expanded
Max Acceleration Throughput	30 Mbps	30 Mbps
Max Edge Cache Throughput	300 Mbps	300 Mbps
Max Accelerated Connections	3,000	6,000

Interface Capabilities	
Built in NICs	3 bypass enabled bridge pairs GigE
Additional NIC Slots	1
Available NICs	2 bridge GigE copper 1 bridge GigE fiber (LC connector)
Management Ports	RJ-45 serial console and dedicated management GigE NIC
IPMI	Present – shared NIC with dedicated management NIC

Physical Characteristics	
Form Factor	1U rackmount with sliding rails included
Dimensions (HxWxD)	44 mm x 436 mm x 300 mm, 1.72" x 16.81" x 11.81"
Power	internal – auto ranging
Power Consumption	17W @ 0.13A (Idle), 22W @ 0.16A (Max)
Weight	5.0 kg, 11 lbs.
Data Store / Cache Size	864 GB
Environment	0°C to 40°C operating temp, 5%-90% operating humidity
Number of VMs supported	1 w/ 4GB RAM, 2 w/ 2GB RAM (maximum shaping throughput 500 Mbps)